

```

=====
Count  RefDes                Value                Description
-----
      5  C23                    .1                   .1 uF 100V 10per RAD
          C24
          C26
          C29
          C30
      1  R31                    1K8                  1K8 OHM .25W 1per RES
      1  D4                      4007                 1KV PIV 1A .5W
      1  R32                    2K4                  2K4 OHM .25W 1per RES
      1  C4                      2.2                  2.2 uF 50 20per EL
      1  R25                    3K3                  3K3 OHM .25W 1per RES
      1  R26                    3K9                  3K9 OHM .25W 1per RES
      1  R34                    6K8                  6K8 OHM .25W 1per RES
      1  R40                    9K1                  9.1K OHM .25W 1per RES
      4  R27                    10                   10 OHM .25W 1per RES
          R28
          R42
          R43
     10  R2                      10K                  10K OHM .25W 1per RES
          R12
          R14
          R21
          R23
          R24
          R35
          R37
          R39
          R41
      2  R1                      18K                  18K OHM .25W 1per RES
          R13
      1  R38                    20K                  20K OHM .25W 1per RES
     28  JW1                     0                    22 GA TINNED COPPER
          JW2
          JW3
          JW4
          JW5
          JW6
          JW7
          JW8
          JW9
          JW10
          JW11
          JW12
          JW13
          JW14
          JW15
          JW16
          JW17
          JW18
          JW19
          JW20
          JW21
          JW22
          JW23
          JW24
          JW25
          JW26
          JW27
          JW28

```

11	C1	22	22 uF 25V 20per EL
	C3		
	C10		
	C11		
	C13		
	C15		
	C16		
	C17		
	C22		
	C27		
	C28		
2	C12	22 pF	22pF 10per Z5F DISK
	C25		
2	R16	30K	30K OHM .25W 1per RES
	R20		
2	C2	50 pF	50pF 10per Z5F DISK
	C21		
2	D2	4148	75V PIV 10mA/1V .5W
	D3		
2	R8	100	100 OHM .25W 1per RES
	R22		
2	C19	100	100 uF 25V 20per EL
	C20		
5	R3	100K	100K OHM .25W 1per RES
	R17		
	R18		
	R19		
	R44		
5	R6	470	470 OHM .25W 1per RES
	R7		
	R9		
	R33		
	R36		
1	C5	2200	2200 uF 16V 20per EL
5	IC1	4560P	4560P DUAL OPAMP
	IC2		
	IC3		
	IC4		
	IC6		
1	JQ1	12V	DPDT 12V RELAY PC MN
1	IC5	LM3915N	LM3915N LED DRIVER
3	JACK1	T/R/S	T/R/S JACK W/GND WASHER
	JACK2		
	JACK3		
1	BRD1	LED BOARD	
1	DZ1	MTG BLOCK	
3	K1	PUSHBUTTON SW	DPDT
	K2		
	K3		
1	VR1	20KA	
1	XLR1	XLR MALE	
1	Z1	20 PIN R/A HEADER	DOUBLE ROW .1" SPACING
1	Z2	10 PIN R/A HEADER	DOUBLE ROW .1" SPACING
1	Z3	4 PIN R/A HEADER	SHROUDED
1	PWB1	06A285-01	LEFT PWB