

Count	RefDes	Value	Description
5	C23 C24 C26 C29 C30	.1	.1 uF 100V 10per RAD
1	R31	1K8	1K8 OHM .25W 1per RES
1	D4	4007	1KV PIV 1A .5W
1	R32	2K4	2K4 OHM .25W 1per RES
1	C4	2.2	2.2 uF 50 20per EL
1	R25	3K3	3K3 OHM .25W 1per RES
1	R26	3K9	3K9 OHM .25W 1per RES
1	R34	6K8	6K8 OHM .25W 1per RES
1	R40	9K1	9.1K OHM .25W 1per RES
4	R27 R28 R42 R43	10	10 OHM .25W 1per RES
10	R2 R12 R14 R21 R23 R24 R35 R37 R39 R41	10K	10K OHM .25W 1per RES
2	R1 R13	18K	18K OHM .25W 1per RES
1	R38	20K	20K OHM .25W 1per RES
28	JW1 JW2 JW3 JW4 JW5 JW6 JW7 JW8 JW9 JW10 JW11 JW12 JW13 JW14 JW15 JW16 JW17 JW18 JW19 JW20 JW21 JW22 JW23 JW24	0	22 GA TINNED COPPER

	JW25		
	JW26		
	JW27		
	JW28		
11	C1	22	22 uF 25V 20per EL
	C3		
	C10		
	C11		
	C13		
	C15		
	C16		
	C17		
	C22		
	C27		
	C28		
2	C12	22 pF	22pF 10per Z5F DISK
	C25		
2	R16	30K	30K OHM .25W 1per RE
	R20		
2	C2	50 pF	50pF 10per Z5F DISK
	C21		
2	D2	4148	75V PIV 10mA/1V .5W
	D3		
2	R8	100	100 OHM .25W 1per
	R22		
2	C19	100	100 uF 25V 20per EL
	C20		
5	R3	100K	100K OHM .25W 1per
	R18		
	R17		
	R19		
	R44		
5	R6	470	470 OHM .25W 1per
	R7		
	R9		
	R33		
	R36		
1	C5	2200	2200 uF 16V 20per EL
5	IC1	4560P	4560P DUAL OPAMP
	IC2		
	IC3		
	IC4		
	IC6		
1	JQ1	12V	DPDT 12V RELAY PC MN
1	IC5	LM3915N	LM3915N LED DRIVER
3	JACK1	T/R/S	T/R/S JACK W/GND WAS
	JACK2		
	JACK3		
1	BRD1	LED BOARD	
1	DZ1	MTG BLOCK	
3	K1	PUSHBUTTON SW	DPDT
	K2		
	K3		
1	VR1	20KA	
1	XLR1	XLR MALE	
1	Z1	20 PIN R/A HEADER	DOUBLE ROW .1" SPACE
1	Z2	10 PIN R/A HEADER	DOUBLE ROW .1" SPACE
1	Z3	4 PIN R/A HEADER	SHROUDED
1	PWB1	06A290-01	RIGHT PWB