

Count	RefDes	Value	Description
10	JW1 JW2 JW3 JW4 JW5 JW6 JW7 JW8 JW9 JW10	0	22 GA TINNED COPPER
2	C6 C8	.1	.1 uF 100V 10per RAD
1	R3	1K8	1K8 OHM .25W 1per RE
2	R26 R27	1M	1M OHM .25W 1per RES
11	R1 R2 R7 R18 R22 R23 R24 R28 R29 R30 R31	10K	10K OHM .25W 1per RE
1	VR1	10KB	
2	R4 R5	18K	18K OHM .25W 1per RE
1	Z2	20 PIN R/A HDR	20 PIN DBL ROW R/A
1	R15	20K	20K OHM .25W 1per RE
3	C3 C11 C12	22	22 uF 25V 20per EL
2	C1 C4	22 pF	22pF 10per Z5F DISK
rev2	R8	22K	22K OHM .25W 1per RE
rev2	R32		
rev2	R33		
2	R6 R25	43K	43K OHM .25W 1per RE
4	R9 R10 R11 R19	47	47 OHM .25W 1per RES
3	R14 R17 R21	47K	47K OHM .25W 1per RE
1	R12	51K	51K OHM .25W 1per RE
3	C5 C7 C10	100	100 uF 25V 20per EL
2	R16	100	100 OHM .25W 1per RE

R20			
3 C2	100 pF		100pF 10per DISK
C9			
C14			
1 C13	470/63V		470 uF 63V 20per EL
3 IC1	4560P		4560P DUAL OPAMP
IC2			
IC3			
1 Q3	A1013		
2 Q1	C1815		
Q2			
2 Q6	J175		J175 P-CH 30Vds 3Vgs
Q7			
1 K1	SPDT		SPDT PC MT TOGGLE SW
1 JACK1	T/R/S		T/R/S JACK W/GND WASHER
1 Q4	TIP-32C		TIP32C PNP -100V 40W
1 Z3	TO FADER	.1	MFSS100-05-T HEADER
1 Z1	10 PIN HEADER		TO POWER SUPPLY
1 Z2	20 PIN R/A HDR		DOUBLE ROW .1" SPACE
1 Z3	4 PIN R/A/ HDR		SHROUDED
1 Z4	10 PIN R/A HDR		DOUBLE ROW .1